



Saiko SFR Series

EXCELLENT WEATHERING & OZONE RESISTANT

HALOGEN-FREE MATERIALS

FLAME RESISTANT UL94-V0 (SELF-EXTINGUISH)

ROSH & REACH COMPLIANCE

SAIKO FLAME RESISTANT (SFR) SERIES HALOGEN-FREE EPDM

SFR Series is a development of Saiko Rubber which provides excellent flame resistance EPDM rubber compound. SFR are able to meet with UL 94-V0 standard requirments, as well as applying with halogen-free materials and able to conform with RoHS & REACH regulation.

SFR are offer a solution for many application widely used in manufacture of automotive and electronic industry.

Typical Properties	SFR EP55-V0		SFR EP70-V0
Hardness (Shore A)	57		74
Tensile (Mpa)	6.9		8.1
Elongation At Break (%)	623		644
Specific Gravity (g/cm)	1.375		1.395
Ozone Resistant	Excellent		Excellent
Flame Resistant	UL94-V0		UL94-V0
Curing Condition	160 Deg C x 10 minutes		160 Deg C x 10 minutes
Curing Agent	Masterbatch	1,000.00 gram	1,000.00 gram
	Sulphur	2.9 gram	2.7 gram
	LDB	5.3 gram	4.8 gram
	CBS	4.4 gram	4.0 gram
	TBzTD	1.8 gram	1.7 gram

SRM A Specialty Rubber Compounding Partner